

Accona

New Range

Timer Panel Heater

0.5, 1.0, 1.5 and 2.0 kW



p.112


Usage

Ideal for a wide range of fixed installation heating applications in the home and office environment.

Features and Benefits

- Stylish curved slimline design
- Available in 0.5, 1.0, 1.5 and 2.0 kW models
- 7 day LCD electronic timer
- Manual or timer operation setting
- Timer configurable in 1 hour slots
- Temperature range 5 - 30°C
- Open window detection
- ErP (Lot 20) compliant
- Power on indicator
- Element on indicator
- Full or half power setting
- Frost protection setting at 5°C
- Easy to use control panel
- IP24 splash - proof
- Integrated child lock
- Wall mounted - secure bracket included
- Slimline - depth only 90mm
- Finished in white

Product Code	Power (kW)	Timer	Current (amps)
AC500T	0.5	Yes	2.2
AC1000T	1.0	Yes	4.3
AC1500T	1.5	Yes	6.5
AC2000T	2.0	Yes	9.0

**Outer Casing**

Powder coated steel

Element

Aluminium x - shape heating element

Controls

Digital controls and screen

Louvres

0.5 and 1.0 kW have two columns of louvres

1.5 kW has three columns of louvres

2.0 kW has four columns of louvres.

Safety

Overheat temperature protection.

IP Rating

IP24

Installation

Wall mounting kit included and must be used.

Electrical Connection

Installation must comply with current IEE regulations.

The product should be connected to the fixed wiring of the property via a double pole fused spur with a minimum break capacity of 13 amps.

Cable pre-wired (1.8m), white cable, entry to the top right of the unit.

Class I

Approvals

CE

Standard Warranty

1 year parts or replacement warranty.

Product Code	Height (mm)	Width (mm)	Depth (mm)	Weight (kg)
AC500T	400	460	90	3.4
AC1000T	400	460	90	3.4
AC1500T	400	595	90	4.7
AC2000T	400	830	90	5.7